

Superior Wood Treating Lumber Spec Sheet

PRODUCT	COMMON USE - APPLICATION	USE CATEGORY SYSTEM (U1)	TREATING PRESERVATIVE & RETENTION	LUMBER TYPE	COLORS AVAILABLE	SIZES AVAILABLE
 LUMBER ABOVE GROUND (AG)	<ul style="list-style-type: none"> SILL PLATE ABOVE GROUND (AG) 	UC3B	ACQ .15 pcf CA-C .06 pcf (KDAT upon request)	Hem-fir graded #2&BTR surfaced four sides (S4S)	Green tone	<ul style="list-style-type: none"> 1x6x6 Fence Boards Brown or 1x4 R/L 2x4 and 2x12, 8' through 20' <i>Other sizes available on request</i>
 ULTRADECK ABOVE GROUND (AG)	<ul style="list-style-type: none"> DECKING SURFACES DECK COMPONENTS ABOVE GROUND (AG) 	UC3B	ACQ .15 pcf CA-C .06 pcf	Hem-fir graded for appearance, surfaced four sides, (S4S)	Brown tone	<ul style="list-style-type: none"> 2x4 and 2x12, 8' through 20' 2x2 4', 8' and 12' balustrade Stair Risers - 2-5 Step
 LUMBER GROUND CONTACT (GC)	<ul style="list-style-type: none"> GROUND CONTACT (GC) FRESH WATER USE 	UC4A	ACQ .40 pcf CA-C .15 pcf	Hem-Fir graded #2&BTR surfaced four sides (S4S)	Brown tone	<ul style="list-style-type: none"> 2x4 through 4x12, 8' through 20' <i>Other sizes available on request</i>
 TIMBERS GROUND CONTACT (GC) & HEAVY DUTY GROUND CONTACT (HD)	<ul style="list-style-type: none"> CONSTRUCTION/ GROUND CONTACT (GC) RESIDENTIAL COMMERCIAL POLE BARN HEAVY DUTY CONSTRUCTION (HD) 	UC4A UC4B	ACQ .40 pcf (GC) CA-C .15 (GC) ACQ .60 pcf (HD) CA-C .31 (HD)	Hem-Fir graded #2&BTR surfaced four sides (S4S) Rough timbers available upon request	Green tone	<ul style="list-style-type: none"> 3x4 through 3x12, 12', 16', 20' 4x4 through 4x12, 8' through 20' 6x6 through 6x12, 8' through 26' 8x8 and 12x12, 8' through 24' <i>Other sizes available on request</i>
 PLYWOOD Above Ground (AG) 	<ul style="list-style-type: none"> ABOVE GROUND (AG) 	UC3B	CCA .25 pcf (KDAT upon request)	CDX	Green tone	<ul style="list-style-type: none"> 1/2", 5/8", and 3/4" 4'x8' sheets <i>Other sizes available on request</i>
 CCA FDN LUMBER (for PWF) Heavy Duty Ground Contact (HD) KDAT	<ul style="list-style-type: none"> PERMANENT WOOD FOUNDATIONS (PWF) LIGHT COMMERCIAL HEAVY DUTY GROUND CONTACT (HD) 	UC4B	CCA .60 pcf (HD) KDAT	Hem-fir graded #2&BTR surfaced four sides (S4S)	Green tone	<ul style="list-style-type: none"> 2x4 and 2x12, 8' through 20' 6x6 and 6x8 , 8' through 26' <i>Other sizes available on request</i>
 CCA FDN PLYWOOD (for PWF) Heavy Duty Ground Contact (HD) KDAT	<ul style="list-style-type: none"> PERMANENT WOOD FOUNDATIONS (PWF) LIGHT COMMERCIAL HEAVY DUTY GROUND CONTACT (HD) 	UC4B	CCA .60 pcf (HD) KDAT	CDX	Green tone	<ul style="list-style-type: none"> 1/2", 5/8", and 3/4" 4'x8' sheets 3/4" and 1-1/8" T&G <i>Other sizes available on request</i>
 LUMBER BORATES	<ul style="list-style-type: none"> ABOVE GROUND INTERIOR USE, CONTINUOUSLY PROTECTED FROM WETTING 	UC2	Borate .25 DOT pcf and .42 DOT pcf (formosan)	Hem-fir/Doug-fir: graded #2&BTR surfaced four sides, (S4S)	Clear	<ul style="list-style-type: none"> 2x4 and 2x6, 12', 14', 16' 2x7 14' <i>Other sizes available on request</i>

WARRANTY*:

- Lifetime limited warranty against fungal decay and termite attack.

*TimberSaver - borates = 20-year transferrable limited warranty against fungal decay and termite attack.

FASTENER REQUIREMENTS**:

- Use code-approved hot-dipped galvanized or stainless steel corrosion-resistant fasteners and G185 hot-dipped galvanized connectors for exterior use.
- Do not mix metals. If using hot-dipped galvanized fasteners, use hot-dipped galvanized connectors. If using stainless steel fasteners, use stainless steel connectors.
- For coastal installations, use code-approved stainless steel.

**TimberSaver-borate treated wood has connector corrosion rates similar or equal to untreated wood; however, building codes require the use of corrosion resistant connectors in contact with all treated wood.



Superior Wood Treating
13702 Stewart Rd.
Sumner, WA 98390

superiorwoodtreating.com
800-422-3120
253-863-4495



treatedwood.com